


Threaded rods, 1 metre

DIN 975 · successor standard DIN 976-1, form A



DIMENSIONS IN MM · MASS FOR STEEL, COARSE THREAD

THREAD D	PITCH P, COARSE	FINE THREAD	LENGTH L	MASS KG / 1000 PCS ≈
M2	0.4	–	1000 ± 10	18.7
M2.5	0.45	–	1000 ± 10	30
M3	0.5	–	1000 ± 10	44
M3.5	0.6	–	1000 ± 10	60
M4	0.7	–	1000 ± 10	78
M5	0.8	–	1000 ± 10	124
M6	1	–	1000 ± 10	177
M8	1.25	M8 × 1	1000 ± 10	319
M10	1.5	M10 × 1.25 · M10 × 1	1000 ± 10	500
M12	1.75	M12 × 1.5 · M12 × 1.25	1000 ± 10	725
M14	2	M14 × 1.5	1000 ± 10	970
M16	2	M16 × 1.5	1000 ± 10	1330
M18	2.5	M18 × 1.5	1000 ± 10	1650
M20	2.5	M20 × 1.5	1000 ± 10	2080
M22	2.5	M22 × 1.5	1000 ± 10	2540
M24	3	M24 × 2	1000 ± 10	3000
M27	3	M27 × 2	1000 ± 10	3850
M30	3.5	M30 × 2	1000 ± 10	4750
M33	3.5	M33 × 2	1000 ± 10	5900
M36	4	M36 × 3	1000 ± 10	6900
M39	4	M39 × 3	1000 ± 10	8200
M42	4.5	M42 × 3	1000 ± 10	9400
M45	4.5	M45 × 3	1000 ± 10	11000
M48	5	M48 × 3	1000 ± 10	12400
M52	5	M52 × 3	1000 ± 10	14700

Mass calculated with a density of 7.85 kg/dm³.

Cut to size. HBS cuts, chamfers and marks studs from rod in-house – configure at hbsfasteners.nl/products/stud-bolts.