



LEGENDS

- s : Width across flats
- e : Width across corners
- m : Height of the Nut
- d : Nominal Diameter fo thread

Thread size d	M1.6	M1.8	M2	M2.5	M3	M3.5	M4	M5	M6	
P	0.35	0.35	0.4	0.45	0.45	0.6	0.7	0.8	1	
da	min.	1.6	1.8	2	2.5	3	3.5	4	5	6
	max.	1.84	2.06	2.3	2.9	3.45	4	4.6	5.75	6.75
dw	min.	2.4	2.7	3.1	4.1	4.6	5.1	5.9	6.9	8.9
e	min.	3.48	3.82	4.32	5.45	6.01	6.58	7.66	9.79	11.05
m	max.	1	1.1	1.2	1.6	1.8	2	2.2	2.7	3.2
	min.	0.75	0.85	0.95	1.35	1.55	1.75	1.95	2.45	2.9
m'	min.	0.6	0.68	0.76	1.06	1.24	1.4	1.56	1.96	2.32
s	max.	3.2	3.5	4	5	5.5	6	7	8	10
	min.	3.08	3.38	3.82	4.82	5.32	5.82	6.78	7.78	9.78

Thread size d		M8	M10	M12	M14	M16	M18	M20	M22	M24
		M8x1	M10x1	M12x1.5	M14x1.5	M16x1.5	M18x1.5	M20x2	M22x1.5	M24x2
		-	M10x1.25	M12x1.25	-	-	M18x2	M20x1.5	M22x2	M24x1.5
P		1.25	1.5	1.75	2	2	2.5	2.5	2.5	3
da	min.	8	10	12	14	16	18	20	22	24
	max.	8.75	10.8	13	15.1	17.3	19.5	21.6	23.8	25.9
dw	min.	11.6	15.6	17.4	20.5	22.5	24.9	27.7	29.5	33.2
	min.	14.38	18.9	21.1	24.49	26.75	29.56	32.95	35.03	39.55
m	max.	4	5	6	7	8	9	10	11	12
	min.	3.7	4.7	5.7	6.42	7.42	8.42	9.1	9.9	10.9
m'	min.	2.96	3.76	4.56	5.14	5.94	6.74	7.28	7.92	8.72
s	max.	13	17	19	22	24	27	30	32	36
	min.	12.73	16.73	18.67	21.67	23.67	26.16	29.16	31	35