



LEGENDS

- s : Width across flats
- e : Width across corners
- m : Height of the Nut
- d : Nominal Diameter fo thread

Thread d	M3	M4	M5	M6	M7	M8	M10	M12	M14	M16	M18	M20	M22	M24	M27	M30	M33	M36	M39	
						M8 x1	M10 x1	M12 x1.5	M14 x1.5	M16 x1.5	M18 x2	M20 x2	M22 x2	M24 x2	M27 x2	M30 x2	M33 x2	M36 x3	M39 x3	
							M10 x1.25	M12 x1.25			M18 x1.5	M20 x1.5	M22 x1.5							
P	0.5	0.7	0.8	1	1	1.25	1.5	1.75	2	2	2.5	2.5	2.5	3	3	3.5	3.5	4	4	
da	min.	3	4	5	6	7	8	10	12	14	16	18	20	22	24	27	30	33	36	39
	max.	3.45	4.6	5.75	6.75	7.75	8.75	10.8	13	15.1	17.3	19.5	21.6	23.7	25.9	29.1	32.4	35.6	38.9	42.1
dv	min.	4.6	5.9	6.9	8.9	9.6	11.6	15.6	17.4	20.5	22.5	24.9	27.7	29.5	33.2	38	42.7	46.6	51.1	55.9
e	min.	6.01	7.66	8.79	11.05	12.12	14.38	18.9	21.1	24.49	26.75	29.56	32.95	35.03	39.55	45.2	50.85	55.37	60.79	66.44
h	max.	3.7	4.2	5.1	6	7	8	10	12	14	16	18	20	22	24	27	30	33	36	39
	min.	3.4	3.9	4.8	5.7	6.5	7.5	9	11	12	14	16	18	20	22	25	28	31	34	37
m	min.	1.65	2.2	2.75	3.3	3.85	4.4	5.5	6.6	7.7	8.8	9.9	11	12.2	13.2	14.8	16.5	18.2	19.8	21.5
s	max.	5.5	7	8	10	11	13	17	19	22	24	27	30	32	36	41	46	50	55	60
	min.	5.32	6.78	7.78	9.78	10.73	12.73	16.73	18.67	21.67	23.67	26.16	29.16	31	35	40	45	49	53.8	58.8