



LEGENDS

- d1** : Inner Diameter
- d2** : Outer Diameter
- h** : Washer Thickness

Nominal Size	Thread	d1		d2		h		weight kg/piece
		Min.	Max.	Max.	Min.	Max.	Min.	
1.7	M1.6	1.7	1.84	4	3.7	0.35	0.25	0.024
1.8	M1.7	1.8	1.94	4.5	4.2	0.35	0.25	0.031
2.2	M2	2.2	2.34	5	4.7	0.35	0.25	0.037
2.5	M2.3	2.5	2.64	6	5.7	0.55	0.45	0.092
2.7	M2.5	2.7	2.84	6	5.7	0.55	0.45	0.088
2.8	M2.6	2.8	2.94	7	6.64	0.55	0.45	0.127
3.2	M3	3.2	3.38	7	6.64	0.55	0.45	0.119
3.7	M3.5	3.7	3.88	8	7.64	0.55	0.45	0.155
4.3	M4	4.3	4.48	9	8.64	0.9	0.7	0.308
5.3	M5	5.3	5.48	10	9.64	1.1	0.9	0.443
6.4	M6	6.4	6.62	12	11.57	1.8	1.4	1.02
7.4	M7	7.4	7.62	14	13.57	1.8	1.4	1.39
8.4	M8	8.4	8.62	16	15.57	1.8	1.4	1.83
10.5	M10	10.5	10.77	20	19.48	2.2	1.8	3.57
13	M12	13	13.27	24	23.48	2.7	2.3	6.27
15	M14	15	15.27	28	27.48	2.7	2.3	8.62

Nominal Size	Thread	d1		d2		h		weight kg/piece
		Min.	Max.	Max.	Min.	Max.	Min.	
17	M16	17	17.27	30	29.48	3.3	2.7	11.3
19	M18	19	19.33	34	33.38	3.3	2.7	14.7
21	M20	21	21.33	37	36.38	3.3	2.7	17.2
23	M22	23	23.33	39	38.38	3.3	2.7	18.3
25	M24	25	25.33	44	43.38	4.3	3.7	32.3
27	M26	27	27.33	50	49.38	4.3	3.7	43.7
28	M27	28	28.33	50	49.38	4.3	3.7	42.3
29	M28	29	29.33	50	49.38	4.3	3.7	40.9
31	M30	31	31.39	56	55.26	4.3	3.7	53.6
33	M32	33	33.62	60	58.8	5.6	4.4	77.4
34	M33	34	34.62	60	58.8	5.6	4.4	75.3
36	M35	36	36.62	66	64.8	5.6	4.4	94.3
37	M36	37	37.62	66	64.8	5.6	4.4	92.1